

MDP SURFACES *

FULL BODY PRINTED QUARTZ



Venatino Grigio UHD-900



























- Vivid & Pure Patterns
- Superior LustreProfound Depth

NEW **LOW SILICA**




















Boticcino UHD-902
























Moscato Beige UHD-903

colour is translucent





- Vivid & Pure PatternsSuperior LustreProfound Depth

NEW **LOW SILICA**





















Calacatta Picasso UHD-904























Marmo UHD-905





- Vivid & Pure Patterns
- Superior LustreProfound Depth

NEW **LOW SILICA**



















Statuario Classico UHD-906
























MATERIALS COMPARISON

MATERIALS	QUARTZ SURFACE	GRANITE	LAMINATE	SOLID SURFACE
Scratch Resistance	* * *	* * *	* *	*
Stain Resistance	* * *	* *	* *	* * *
Chip & Crack Resistance	* * *	* *	* *	* * *
Heat & Burn Resistance	* *	* *	* *	* *
Resistance to Household, Chemicals, Acids & Solvent	* * *	* *	**	* * *
Low Maintenenace	* * *	* *	* *	*
Non-absorbency & Non-porosity	* * *	* *	* *	* * *
Mold & Mildrew Resistance	* * *	* *	* *	* *
Flexural Strength	* * *	*	* *	* *
Colour Consistency	* * *	*	* * *	* * *
Immunity to Freeze & Thaw	* * *	* * *	*	*







TECHNICAL SPECIFICATIONS

SPECIFICATIONS	TEST METHOD	RESULTS	
Water Absorption (% by weight)	ASTM C97/C97M-09:2009	≤ 0.05%	
	BS EN 14617-1:2013	≤ 0.06%	
Apparent Density	ASTM C97/C97M-09:2009	2.2 – 2.4 gr/cm ³	
	BS EN 14617-1:2013	2.2 – 2.4 gr/cm ³	
Flexural Strength	ASTM C880/C880M-09:2009	> 40 MPa	
	BS EN 14617-2:2016	> 40 MPa	
Compressive Strength	ASTM C170/C170M-09:2009	≥ 155 MPa	
	BS EN 14617-15:2005	≥ 155 MPa	
Chemical Resistance	ASTM C650-04:2014	Unaffected	
	BS EN 14617-10:2012	Class C ₄	
Dimension Stability	EN 14617-12:2012	Class A	
Electrical Stability	EN 14617-13:2013	Volume resistance (RV) = $0.9 \times 10^{14}\Omega$,	
		Volume resistance (pV) = $4.88 \times 10^{14} \Omega \text{m}$	
Impact Resistance	ASTM D1709:2015	≥ 3.0 J	
	EN 14617-9:2005	≥ 3.0 J	
Abrasion Resistance	ASTM C501-84:2015	Abrasive Wear index: lw ≥ 179	
	BS EN 14617-4:2012	Volume of chord: V ≤ 195 mm ³ , Chord length: I ≤ 27 mm	
Thermal Shock Resistance	ASTM C484-99:2014	No visible damage after 10 cycles	
	EN 14617-6:2012	No visible defects after 20 cycles, Change in mass: ≤ 0.05%,	
		Change in flexural strength: 8.4% ÷ 5.4%	
Freeze-thaw Resistance	ASTM C1026-13:2018	No visible damage after 300 cycles, Wt.Loss: ≤ 0.09%	
	EN 14617-5:2012	No obvious damage after 20 cycles, KMf25 = 93 ÷ 105%	
Mohs Scale of Hardness	EN 101	6.0 - 7.0	
Slip Resistance	DIN 51130:2014	R9 at Honed 400	
	ASTM C1028-07	Static coefficient of friction - Dry: 0.7 ÷ 0.8 (Polished/Honed finish),	
		Wet: 0.5 ÷ 0.7 (Polished/Honed finish)	
Microbial Resistance	ASTM D6329:2015	Ranking 3: Resistant to Mold Growth	
Stain Resistance	ASTM C1378-04:2014	Class A (Polished finish)	
Surface Burning	ASTM E84	Class A	
Determination of Resistance	AS 2924.2-8:1998 (equi. to	Effect on surface rating: 5	
to Immersion in Boiling Water	ISO 4586.2-8:1997)	(no visible change)	
Determination of Resistance	AS 2924.2-8:1998 (equi. to	Effect on surface rating: 5	
to Dry Heat	ISO 4586.2-8:1997)	(no visible change)	
Determination of Resistance	AS 2924.2-15:1998 (equi. to	Effect on surface rating: 5	
to Staining (Procedure A)	ISO 4586.2-15:1997)	(no visible change)	



FULL BODY PRINTED QUARTZ



WHAT IS LASER-PRINTED QUARTZ?

Laser-printed quartz countertops use advanced laser technology to create detailed patterns on engineered quartz surfaces. This four stage method enhances the aesthetic appeal, the consistency of design and the durability of quartz countertops, making them look more natural and unique.

Quartz Slab Base: The process begins with a raw quartz slab serving as the foundation.

High-Resolution Image (HighD): A digitally designed pattern is prepared for transfer onto the quartz surface.

High-Temperature Application: The slab is heated to 280°C, allowing the image's colours and design to bond with the quartz.

Colour Transfer Process: Using a heat transfer method similar to sublimation, the high temperature enables the image to adhere permanently to the quartz surface.













